

Integrated One-stop Solution For Your Business Expansion

Designed as a central hub of POS to connect displays, tablets, network and various payment terminals. The TS1 is a multi-functional countertop transformer which has created a convenient platform for various merchants to custom-make their own POS station at shops.























Specification	S			
		For SP53	0 mPOS	For T300 mPOS
Memory	Flash RAM	8/16MB 256KB		128MB 64MB
Card slots	SAM Micro SD SIM	Max. 1 (optional) 1 (optional) -		Max. 2 (optional) - 2 (optional)
Overall weight (Excluded paper roll)		no batte 3.7kg, w	mer LCD & ry	3.4kg (no battery) 3.6kg (with battery)
Payment acceptance types	Magnetic track 1/2/3 EMV NFC Contactless (optional)			
Processor	ARM® Cortex® secure processor			
Display	8"-15" Android or Windows®			
Second display	7" LCD (optional)			
Thermal printer	Type: Printing speed: Paper roll:		3" Thermal with auto-cutter Max. 250mm/sec 80mm diameter	
Keys	1 (On/off switch)			
Communication interface	Ethernet			
Peripheral	RS232 x 1 USB host port x 4		USB 2.0 x 1	
Audio	Speaker x 1			
Battery	2500mAh x 4 (optional)			
Power supply	DC jack for 24V power input, 100~240 AC, 50/60Hz			
Certifications	PCI PTS Visa PayWave SRED TQM		EMV L1 & L2 MasterCard Contactless QPBOC FCC/CE	
	JCB J/Speedy	<u>os</u>	American E	Express ExpressPay
Operating temperature	0 - 45°C			
Storage temperature	-20 - 70 °C			
Operating humidity	5-95% non-condense			







TS1 with T300



*Specifications is subject to change without prior notice.

Dimensions

SPECTRA Technologies Holdings Co. Ltd.

350 (L) x 186 (W) x 290 (H) mm

